

LGR

LAME CIRCOLARI HM CON RASANTI

Lame circolari in metallo duro per sezionatura di assi per bancali o imballi, tavolame in genere, travi per tetti e carpenteria pesante in legno. Utilizzabili su macchine multilama, rifilatrici, impianti per segheria e centri di lavoro per travi e tavolame.

TCT CIRCULAR SAW BLADES WITH CARBIDE SCRAPERS

Tct circular saw blades to section planks for pallets of packages, common boards, roof beams and wood heavy carpentry. Useful on multi-blade machines, trimming machines, sawmill equipments and working centres for beams and common boards.



DIAMETRO DIAMETER	SPESSORE THICKNESS	FORO HOLE	DENTI TEETH	CODICE CODE
250	2,8	a richiesta / on request	20+4	LGR.
300	3,2	a richiesta / on request	24+4	LGR.
320	3,2	a richiesta / on request	24+4	LGR.
350	3,5	a richiesta / on request	28+4	LGR.
400	4,0	a richiesta / on request	18+4	LGR.
400	4,0	a richiesta / on request	24+4	LGR.
500	4,4	a richiesta / on request	22+4 - 6	LGR.
500	4,4	a richiesta / on request	28+4 - 6	LGR.
735	6,0	a richiesta / on request	48+6	LGR.
735	6,0	a richiesta / on request	72+6	LGR.
760	6,0	a richiesta / on request	48+6	LGR.
760	6,0	a richiesta / on request	72+6	LGR.
800	6,0	a richiesta / on request	48+8	LGR.
800	6,0	a richiesta / on request	72+8	LGR.

a richiesta: altre misure/on request: other sizes